


KOMPAKT

**6x19 Seale + IWRC, VERDICHTET,
in Anl. an EN 12385-4,
Kreuzschlag, 1960 N/mm²**


Seil-Ø mm	MBK kN	kg
6,00	34,2	19,6
7,00	44,7	25,6
8,00	56,5	32,4
9,00	76,9	44,1
10,00	92,3	52,9
11,00	109	62,5
12,00	127	72,9
13,00	147	84,1
14,00	168	96,1
15,00	179	102,4
16,00	226	130,0
18,00	279	160,0
20,00	338	194,0
22,00	402	237,0



GRIZZLY

**6x25 Filler +IWRC, VERDICHTET,
in Anl. an EN 12385-4,
Kreuzschlag, 1960 N/mm²**


Seil-Ø mm	MBK kN	Gewicht/100 m kg
8,00	56,5	32,4
9,00	76,9	44,1
10,00	92,3	52,9
11,00	109	62,5
12,00	127	72,9
13,00	147	84,1
14,00	168	96,1
15,00	179	102,4
16,00	226	130,0
18,00	279	160,0



KOMPAKT-PREMIUM

**6x19 Seale + IWRC, VERDICHTET,
in Anl. an EN 12385-4,
Kreuzschlag, 2160 N/mm²**

Seil-Ø mm	MBK kN	Gewicht/100 m kg
8,00	71,3	36,1
9,00	87,1	44,1
10,00	104,4	52,9
11,00	123,4	62,5
12,00	143,9	72,9
13,00	166,0	84,1



GRIZZLY-PREMIUM

**6x25 Filler +IWRC, VERDICHTET,
in Anl. an EN 12385-4,
Kreuzschlag, 2160 N/mm²**

Seil-Ø mm	MBK kN	Gewicht/100 m kg
8,00	71,3	36,1
9,00	87,1	44,1
10,00	104,4	52,9
11,00	123,4	62,5
12,00	143,9	72,9
13,00	166,0	84,1